

MONOAXLE TRAILERS WITH TRYLATERAL HYDRAULIC TIPPING SYSTEM

TECHNICAL FEATURES

- 3-way hydraulic tipping by means of flexible hose and quick coupling
- Platform floor in stamped or smooth steel sheet
- Hinged and removable dropping type lateral sideboards
- Two-ways opening rear sideboard
- Two-lines pneumatic brake with load sensing device *
- Mechanical parking brake and adjustable parking jack

- Rear underrun protection bar
- Rear and lateral led position lights (where provided by regulation) *
- 12 volt lightening equipment including stop and direction lights

*Except art. ER25SF, which has no brake



Accessori a richiesta:

- Doppie sponde
- Apertura sottosopra sponde laterali Occhione con altezza variabile
- Scaletta
- Bocchetta posteriore
- Ruota di scorta con supporto

OMOLOGAZIONE EUROPEA N. e24*167/2013*00295 – 00296 - 00300

MODELLO	DIMENSIONI PIANALE mm	CAPACITÀ MASSIMA DI CARICO SULL'ASSE Kg	CAPACITÀ MASSIMA DI CARICO SULL'OCCHIONE Kg	CAPACITÀ TOTALE DI CARICO DEL RIMORCHIO Kg	PESO A VUOTO Kg	DIMENSIONI FRENI mm	RUOTE
Velocità Massima 30 km/h - Sospensioni Rigide - Freno Pneumatico con correttore manuale							
ER25SF	2500x1500	1500	400	1900	540	No brake*	10.0.75.15.3 12pr
ER2735	2700x1700	3500	700	4200	740	300x60	10.0.75.15.3 12pr
ER2935	2900x1800	3500	800	4200	800	300x60	10.0.75.15.3 12pr
ER2950	2900x1800	5000	1000	6000	850	300x90	11.5/80-15.3 16pr
ER3450	3400x2000	5000	1000	6000	1130	300x90	11.5/80-15.3 16pr
ER3750	3700x2000	5000	1000	6000	1200	300x90	11.5/80-15.3 16pr
ER4050	4000x2200	5000	1000	6000	1300	300x90	11.5/80-15.3 16pr
Velocità Massima 40 km/h - Sospensioni a balestra - Freno Pneumatico con correttore automatico							
ER4080	4000x2200	8000	1500	9500	1700	300x135	435/50 r19,5 reg.
ER4580	4500x2200	8000	1500	9500	1780	300x135	435/50 r19,5 reg.
ER45100	4500x2200	10000	1600	11600	1850	400x120	435/50 r19,5 reg.
ER50100	5000x2200	10000	1600	11600	2000	400x120	435/50 r19,5 reg.
ER5010L	5000x2200	10000	1600	11600	2100	400x120	435/50 r19,5 reg.

* Cavo di sicurezza sull'occhione