

# MULTI-PURPOSE MONOAXLE PLATFORM TRAILERS

## TECHNICAL FEATURES

- Steel construction of chassis and platform
- Front double effect hydraulic cylinder for rear tipping
- Leaf spring suspensions
- Platform with or without lateral sideboard
- Platform with or without non-slip iron rods
- Front removable side and rear amp for an easier load of machines
- 2-lines pneumatic brake with load sensing device
- Mechanical parking brake
- Bolted or turning type towing eyes
- Lateral and front winches or fastening holes
- Mechanical parking stand
- Rear underrun protection bar
- Rear and lateral led position lights
- 12 volt lightening equipment including stop and direction lights
- Nr 1 tool box
- Nr 2 wheel stoppers

Adatto al trasporto di grandi volumi, escavatori, cingolati, macchine agricole, balloni, box per frutta



### Accessori a richiesta:

- Telaio anteriore e posteriore
- Piedino idraulico
- Vernice Bicomponente
- Fori laterali anziché verricelli
- Boccole porta palo ricavate nel pianale
- Aste laterali

OMOLOGAZIONE UE N° e24\*167/2013\*00297

MODELLO	DIMENSIONI PIANALE mm	RUOTE GEMELLE*	PESO NETTO Kg
Massimo carico su asse 8000kg - Massimo carico su occhione girevole 1500kg			
EP4908	4900x2400	235/75 R 17.5	1700
EP5508	5500x2400	235/75 R 17.5	2100
EP6108	6100x2400	235/75 R 17.5	2350
Massimo carico su asse 10000kg Massimo carico su occhione girevole 2000kg			
EP4910	4900x2550	245/70 R 17.5	1800
EP5510	5500x2550	245/70 R 17.5	2200
EP6110	6100x2550	245/70 R 17.5	2450

\* riscalpite - Pneumatici diversi (anche singoli) disponibili su richiesta