

TANDEM TRAILERS WITH TRILATERAL HYDRAULIC TIPPING

TECHNICAL FEATURES

- Three-way hydraulic tipping with quick coupling and flexible hose
- Steel construction of chassis and platform
- Platform floor in stamped or smooth steel sheet
- Pronar type sides
- Tipping system with cut-off valve
- N. 2 pins for selection of the right tipping direction
- Double leaf spring suspensions
- 2-lines pneumatic brake with load sensing device
- V-type drawbar with turning or fixed towing eye
- Hinged and removable dropping type lateral sides
- Lateral sides divided in two pieces by central pillar
- Central (2-ways) opening rear and lateral sides
- Mechanical parking brake
- Adjustable parking stand
- Grain hatch, access ladder, rear mudflaps, wheel chocks and racks
- Rear underrun protection bar if approved at 40 km/h
- Rear and lateral underrun protection bar if approved at 60 km/h
- Led lightening equipment including lateral position lights
- Tool box



Accessori a richiesta:

- Telaio per copertura (senza telone) e piattaforma operatore
- Copertura industriale
- Supporto con ruota di scorta
- Scarico a coclea
- Occhione ad altezza regolabile

OMOLOGAZIONE UE N° e24*167/2013*00368*00 - omologato PER 60 o 40 km/h

MODELLO	DIMENSIONI MT	GOMME STANDARD	MASSIMO CARICO SULL'ASSALE	MASSIMO CARICO (ASSALE + OCCHIONE)
BT14-45-5	4.50x2.20x (0,50+0,50)	400/60-15.5 16PR	14 Tonnellate	16 Tonnellate
BT14-45-6	4.50x2.20x (0,60+0,60)	435/50 R 19.5	14 Tonnellate	16 Tonnellate
BT18-50-6	5.00x2.30 (0,60+0,60)	385/55 R 22.5	18 Tonnellate	20 Tonnellate
BT18-50-8	5.00x2.30 (0,80+0,60)	385/65 R 22.5	18 Tonnellate	20 Tonnellate