

SINGLE AXLE TRAILERS WITH THREE WAY HYDRAULIC TIPPING

TECHNICAL FEATURES

- Trilateral hydraulic tipping by means of quick coupling and flexible hose
- Platform floor in stamped or smooth steel sheet
- Mechanical brake
- Adjustable parking jack
- Lightening system
- Powder painted or hot dip galvanized steel sides
- Various options of customization



MODEL	DIMENSIONS (Mt.)	MAXIMUM LOAD ALLOWED (Kg.)	TRAILER WEIGHT (Kg.)	TYRES
BRT125P	2.30x1.50x0.40	2000	520	205.15 D
BRT125G CF	2.50x1.50x0.40	2500	560	205.15 D
BRT220	2.50x1.60x0.40	3000	580	10.0/80 12 10pr
BRT225	2.70x1.70x0.40	3500	690	10.0/75 15.3 10pr
BRT228	2.90x1.80x0.40	4000	740	10.0/75 15.3 12pr
BRT40	3.20x1.90x0.40	5000	910	11.5/80 15.3 12pr
BRT552	3.00x1.80x0.50	5000	1000	285/70 R19.5
BRT550	3.40x2.00x0.50	6000	1100	11.5/80 15.3 14pr
BRT552 L	3.50x1.80x0.50	6000	1120	285/70 R19.5
BRT555	3.70x2.00x0.50	7000	1140	11.5/80 15.3 14pr
BRT555G	3.70x2.00x0.50	7000	1220	215/75 R17.5 I gem
BRT502C	4.00x2.00x0.50	8000	1315	215/75 R17.5 I gem
BRT502L	4.00x2.20x0.50	8000	1260	13.0/65 18 16pr